

TT-DVR5108

8 CH DVR



SPECIFICATIONS:

Model	TT-DVR5108
Operating System	Linux 2.6 O/S Pentaplex operation: record, playback, preview and network browse, backup supported.
I/O Interface	
Video Input	8 channel, BNC, 1Vp p 75Ω PAL (625 line, 50 f/s), NTSC (525 line, 60 f/s), SECAM(625 line, 50 f/s)
Audio Input	4 channel, RCA, 2Vp p 600Ω
VGA Output	1channel, DIN 15(optional); 800×600@60Hz 1024×768@60Hz 1280×1024@60Hz 1440×900@60Hz
CVBS Output	1 channel, BNC, 1Vp p,75Ω
Audio Output	1 channel, RCA, 2Vp p, 600Ω
USB Interface	Support USB storage device, USB mouse, USB burner.
RS422	1 port, receiving and transmitting duplex supported.
Network Interface	RJ45 , 10/100M self adaptive
Alarm Input	4 channel NO/NC
Alarm Output	1 channel NO/NC, relay: 30VDC 1A to 125VAC 1A
SATA Interface	1 SATA port, 1 SATA HDD up to 1Tsupported.
Video & Audio	
Video Compression	H.264 Baseline
Video Standards	PAL/NTSC/SECAM
Video Compression Resolution	PAL:352×288 CIF NTSC: 352×240 CIF PAL:704×288 Half D1/2CIF NTSC:704×240 Half D1/2CIF PAL:704×576 D1/4CIF NTSC: 704×480 D1/4CI F
Frame Rate	PAL: 25F/S/CH 1, 3, 6, 12, 25 and user defined optional, NTSC: 30F/S/CH 1, 3, 7, 15, 30and user defined optional.
Video Output Bit Rate	32kbps 2048kbps 14M byte/hour 922M byte/hour
Preview Resolution	PAL 720×576 D1 horizontal line 550, vertical line 450 NTSC 720×480 D1 horizontal line 550, vertical line 400
Playback Resolution	PAL: 352×288 CIF horizontal line 300, vertical line 250 NTSC: 352×240 CIF horizontal line 300, vertical line 220
Audio Compression	G.726 ADPCM
Input/output Sampling Rate	8KHz
Audio Channel Type	Mono
Sampling Bit	16 bit
Power Supply	DC 12V 3/5A
Power Consumption	12W without HDD

NOTE: ADINO TELECOM LTD reserves the right, without notification, to make changes in product design or specifications