

Indoor Plastic Color Dome

ADINO**CCTV***Stay Connected Stay Ahead*

TT-HLDN60P-S

Key Features:

- 1/3" CCD Image Sensor
- 600 TVL High Resolution
- 3.6mm Fixed Lens
- WDR, HLC, Motion detection
- Privacy masking function
- Built in Digital Signal Process



SPECIFICATIONS:

Model	TT-HLDN60P-S
Signal System	NTSC PAL
Image Device	1/3" Sony CCD
Effective Pixel	768(H) x494 (V) / 752 (H) x582 (V)
Horizontal Resolution	600 TVL
Lens	3.6mm Fixed Lens
Signal/Noise Ratio	More than 50dB
Sync System	Inner
Shutter Speed	1/60-1/10,000 (Selectable) / 1/50-1/10,000 (Selectable)
Min Illumination	0.01Lux/F1.2
Auto Exposure	Automatic Level Control (ALC) / Electronic Level Control (ELC)
WDR	On / Off
Motion Detection	4 Zone
Privacy Masking	4 Zone
Scanning System	2.1 interlaced
Scanning frequency	15.734 KHz(H), 60Hz(V) / 15.625 KHz(H), 50Hz(V)
Noise Reduction	DNR, more than 50 dB
BLC	On / Off / Low / Medium / High
Gamma Correction	0.45
Signal System	Digital Signal Processing
OSD	Yes
White Balance	Indoor / Outdoor / Manual
AGC	On / Off / Low/ Medium / High
Video Output Signal	1V p-p Composite video (75 Ohms)
Day & Night	Yes
Operating Temp	-10°C ~ 50°C
Power Consumption	Max 2.5 W
Power Supply	DC 12V Adaptor Input Voltage 230V AC ±10%

NOTE: ADINO TELECOM LTD reserves the right, without notification, to make changes in product design or specifications